

Technical Data

Product: Central Vacuum Supply System CVS 500 – incl. 2 x SOGEVAC SV 300 B
Part No.: 504312V054

Volume vacuum vessel:	500 l
Installed vacuum pump:	2 x SOGEVAC SV 300 B
Inlet connection vacuum vessel:	G 2", Inside thread
Outlet connection:	G 2", Inside thread
Nominal pumping speed at 50 Hz:	560 m ³ /h
Nominal pumping speed at 60 Hz:	680 m ³ /h
Pumping speed at 50 Hz:	480 m ³ /h
Pumping speed at 60 Hz:	580 m ³ /h
Ultimate total pressure without gas ballast:	≤ 0,08 mbar
Ultimate total pressure with gas ballast:	≤ 0,7 mbar
Water vapor tolerance at 50 Hz:	10 mbar
Water vapor tolerance at 60 Hz:	12 mbar
Water vapor capacity at 50 Hz:	2600 g/h
Water vapor capacity at 60 Hz:	3600 g/h
Operating fluid:	LVO 130
Operating fluid capacity:	22 l
Noise level to DIN 45 635:	75 dB(A), without gas ballast
Mains connection:	3-ph, 400 V, 50 Hz // 460 V, 60 Hz
Installed motor rating at 50 Hz:	11 kW
Installed motor rating at 60 Hz:	13,2 kW
Electrical control:	Full Feature-Controller
Admissible ambient temperature:	+12 to +40°C
Dimensions (LxBxD):	1976 x 1159 x 1480 mm
Weight:	750 kg

Technical data are subject to change